



SUNPOWER TECHNOLOGY CORP.
16F-1, No.150, Jian 1st Rd., Zhonghe Dist., New Taipei City 235, Taiwan (R.O.C.).
TEL: 886-2-8226-3100 FAX: 886-2-8226-3111
http://www.sunpower.com.tw
E-mail: sunpower@sunpower.com.tw

SPS-070 -xx Series

SPS-070P-xx Series

72 W, Single Output
P.F.C Function Optional



159 x 95 x 38 mm
6.26 x 3.74 x 1.50 inch



Features:

- * Green-mode design, no load < 0.75W
- * High reliability and high efficiency
- * Power ON with LED indicator
- * Over voltage protection
- * Over load & short circuit protection
- * Output voltage $\pm 10\%$ adjustment
- * 100% full load burn-in test
- * UL, cUL, TUV, CB, CE approved
- * 3 years warranty

Specification:

INPUT	Voltage	85V ~ 264VAC universal full range or 120V ~ 375VDC.					
	Frequency	47 ~ 63 Hz					
	Current	<1.8A @100V AC input, full load condition					
	Inrush Current	<30A@115V , <60A@230V AC input. Cold start at 25°C ambient					
	Leakage Current	<1.0mA@264V AC input					
OUTPUT	MODEL No.	SPS-070 -3.3 SPS-070P-3.3	SPS-070 -05 SPS-070P-05	SPS-070 -12 SPS-070P-12	SPS-070 -15 SPS-070P-15	SPS-070 -24 SPS-070P-24	SPS-070 -48 SPS-070P-48
	Voltage	3.3V	5V	12V	15V	24V	48V
	Min Load	0A	0A	0A	0A	0A	0A
	Max Load	15A	12A	6A	4.8A	3A	1.5A
	Output Tolerance ②	$\pm 3\%$	$\pm 2\%$	$\pm 1\%$	$\pm 1\%$	$\pm 1\%$	$\pm 1\%$
	Ripple Noise MAX. ③	70mV	70mV	120mV	150mV	200mV	250mV
	Efficiency (TYP.)	74%	77%	82%	83%	84%	86%
PROTECTION	Output MAX.	50W	60W	72W	72W	72W	72W
	Over Voltage	3.8~4.6V	5.8~7.0V	13.8~16.8V	17.3~21.0V	27.6~33.6V	55.2~67.2V
	Over Load & Short Circuit	Shutdown and latch off, recover after re-start up. When power supply over 105%~ 150% max load or short circuit acted, power supply will go into hiccup mode and recover automatically after the fault is removed.					
ELEC. CHAR.	Rise time	<20mS					
	Hold up time	>16.7mS@115V , >60mS@230V					
	Setup time	<1 Sec@100 ~ 240V AC					
ENVIRONMENT	Green mode function	Power consumption at no load < 0.75W					
	Temperature ④	Operating: -20 ~ 70°C ; De-rating: 45 ~ 70°C : 2.5%/°C ; Storage: -40 ~ +85°C					
	Humidity	Operating: 20% ~ 90%; Storage: 10% ~ 95% (non condensing)					
SAFETY	Withstand voltage	I/P-O/P:3KVAC, I/P-PE:1.5KVAC, O/P-PE:0.5KVDC, 1minute					
	Isolation resistance	I/P-O/P, I/P-PE, O/P-PE > 100MΩ/500VDC at 25°C/ 70% RH					
	Safety standard	UL 60950-1 2 nd , CSA C22.2 No. 60950-1-07 2 nd , TUV EN 60950-1:2006+A11, IEC 60950-1:2005, approved.					
EMC	EMI	EN 55022 CLASS B - FCC CFR 47 PART 15 CLASS B - CNS 13438 CALSS B. Compliance to EN61000-3-2 CLASS A, EN61000-3-3, SPS-070P-xx models are built-in PFC choke to lower 25% THD (Total Harmonic Distortion) performance,					
	EMS	EN 55024 : EN 61000-4-2,3,4,5,6,8,11					
	OTHERS						
OTHERS	Cooling	Natural cooling.					
	M.T.B.F.	300K hours at 25°C					
	Terminal pitch	7P / 9.5mm with plastic cover, 90 deg terminal optional (with MOQ)					
NOTE	Packing	N.W.:0.6Kg / 1pc; 30pcs / 1.20 CUFT / 1 CTN					
	①	All measurements which not mentioned are based on 230VAC input, output Max at ambient 25°C / 70%RH					
	②	Output tolerance included set up voltage, line regulation and load regulation.					
NOTE	③	Ripple & noise are measured at 100~254VAC input with 10~50°C condition and 20MHz of bandwidth by using a 10" ~ 15" twisted pair-wire terminated with a 0.1uF & a 47uF parallel capacitor.					
	④	The operating temperature shall follow the de-rating curve in spec The output load may be requested for decreasing as de-rating curve in spec when low input voltage is under 100VAC					
	⑤	The power supply is considered a component of end-equipment. The end-equipment must be re-confirmed whether comply with EMC directives.					




SUNPOWER TECHNOLOGY CORP.
 16F-1, No.150, Jian 1st Rd., Zhonghe Dist., New Taipei City 235, Taiwan (R.O.C.).
 TEL: 886-2-8226-3100 FAX: 886-2-8226-3111
<http://www.sunpower.com.tw>
 E-mail: sunpower@sunpower.com.tw


SPS-070 -xx Series

SPS-070P-xx Series


Block Diagram : US3



De-rating Curve :




Output De-rating Vs Input Voltage :



Dimension:

(Unit: mm)



NOTES:

TERMINAL BLOCK: 7P, PITCH 9.5mm WITH PC COVER.

MODEL No.	1	2	3	4	5	6	7
SPS-070(P) -xx	L	N	PE	-V	-V	+V	+V