



APPLICATIONS

Wireless Network
Telecom/Datacom
Industry Control System
Measurement Equipment
Semiconductor Equipment

FEATURES

- 40 WATTS MAXIMUM OUTPUT POWER
- OUTPUT CURRENT UP TO 8A
- STANDARD 2.00 X 2.00 X 0.40 INCH PACKAGE
- HIGH EFFICIENCY UP TO 90%
- 2:1 WIDE INPUT VOLTAGE RANGE
- SIX-SIDED CONTINUOUS SHIELD
- FIXED SWITCHING FREQUENCY
- OFFER SINGLE, DUAL, DUAL POSITIVE (TOTAL OUTPUT CURRENT 8A) AND TRIPLE OUTPUT
- CE MARK MEETS 2006/95/EC, 93/68/EEC AND 2004/108/EC
- UL60950-1, EN60950-1 AND IEC60950-1 LICENSED
- ISO9001 CERTIFIED MANUFACTURING FACILITIES
- COMPLIANT TO RoHS EU DIRECTIVE 2011/65/EU

DESCRIPTION

The FEC40 series offer 40 watts of output power from a 2.00 x 2.00 x 0.40 inch package. The FEC40 series with 2:1 wide input voltage of 9~18VDC, 18~36VDC and 36~75VDC and features 1600VDC of isolation, short-circuit and over-voltage protection.

TECHNICAL SPECIFICATION

All specifications are typical at nominal input, full load and 25°C otherwise noted

OUTPUT SPECIFICATIONS			
Output power		40 Watts, max.	
Voltage accuracy	Single / Dual Triple Main Auxiliary	± 1% ± 1% ± 5%	
Minimum load (Note 6)		See Table	
Voltage adjustability (Note 7)	Single and Dual output only (not including Dual Positive and triple)	± 10%	
Line regulation LL to HL at Full Load	Single/Dual Triple main Auxiliary	± 0.5% ± 1% ± 5%	
Load regulation (Note 8)	Min. Load to Full Load Single Dual Triple Main Auxiliary	± 0.5% ± 1% ± 2% ± 5%	
Load cross regulation (Note 9)	Triple(main) Dual/Triple(auxiliary)	± 1% ± 5%	
Ripple and noise (Note 10)	20MHz bandwidth (Measured with a 0.1µF/50V MLCC)	See table	
Temperature coefficient		±0.02% / °C, max.	
Transient response recovery time	25% load step change	250µs	
Over voltage protection Zener diode clamp	1.5VDC output 1.8VDC output 2.5VDC output 3.3VDC output 5VDC output 12VDC output 15VDC output	3.9VDC 3.9VDC 3.9VDC 3.9VDC 6.2VDC 15VDC 18VDC	
Over load protection	% of FL at nominal input	150%, max.	
Short circuit protection		Hiccup, automatic recovery	
GENERAL SPECIFICATIONS			
Efficiency		See table	
Isolation voltage	Input to Output Input(Output) to Case	1600VDC, min. 1minute 1600VDC, min. 1minute	
Isolation resistance		10 ⁹ ohms, min.	
Isolation capacitance		1000pF, max.	
Switching frequency (Note 11)		300KHz±10%	
Approvals and standard		IEC60950-1, UL60950-1, EN60950-1	
Case material		Nickel-coated copper	
Base material		FR4 PCB	
Potting material		Epoxy (UL94-V0)	
Dimensions		2.00 X 2.00 X 0.40 Inch (50.8 X 50.8 X 10.2 mm)	
Weight		60g (2.11 oz)	
MTBF (Note 1)	BELLCORE TR-NWT-000332 MIL-HDBK-217F	1.398 x 10 ⁶ hrs 3.585 x 10 ⁵ hrs	

INPUT SPECIFICATIONS			
Input voltage range	12VDC nominal input 24VDC nominal input 48VDC nominal input	9 ~ 18VDC 18 ~ 36VDC 36 ~ 75VDC	
Input filter		L-C type	
Input surge voltage	12VDC input 24VDC input 48VDC input	36VDC 100mS, max. 50VDC 100mS, max. 100VDC 100mS, max.	
Input reflected ripple current		40mA p-p	
Start up time	Nominal input and constant resistive load	Powe up 25mS Remote ON/OFF 25mS	
Start-up voltage	12VDC input 24VDC input 48VDC input	9VDC 17.8VDC 36VDC	
Shutdown voltage	12VDC input 24VDC input 48VDC input	8VDC 16VDC 34VDC	
Remote ON/OFF (Note 12) (Positive logic)	DC-DC ON DC-DC OFF	Open or 3.5V < Vr < 12V Short or 0V < Vr < 1.2V	
Input current of remote control pin	Nominal input	-0.5mA~+0.5mA	
Remote off state input current	Nominal input	2.5mA	
ENVIRONMENTAL SPECIFICATIONS			
Operating ambient temperature		-40°C ~ +85°C (with derating)	
Maximum case temperature		+100°C	
Storage temperature range		-55°C ~ +105°C	
Over temperature protection		115°C	
Thermal impedance (Note 13)	Natural convection Heat-sink with 20LFM Heat-sink with 500LFM	9.2°C/Watt 7.6°C/Watt 2.8°C/Watt	
Thermal shock		MIL-STD-810F	
Vibration		MIL-STD-810F	
Relative humidity		5% to 95% RH	
EMC CHARACTERISTICS			
EM I (Note 14)	EN55022		Class A
ESD	EN61000-4-2	Air ± 8KV Contact ± 6KV	Perf. Criteria B
Radiated immunity	EN61000-4-3	10 V/m	Perf. Criteria A
Fast transient (Note 15)	EN61000-4-4	± 2KV	Perf. Criteria B
Surge (Note 15)	EN61000-4-5	± 1KV	Perf. Criteria B
Conducted immunity	EN61000-4-6	10 Vr.m.s	Perf. Criteria A










Model Number	Input Range	Output Voltage	Output Current		Output ⁽⁴⁾ Ripple & Noise	Input Current		Eff ⁽⁴⁾ (%)	Capacitor ⁽⁵⁾ Load max
			Min. load	Full load		No load ⁽³⁾	Full load ⁽²⁾		
FEC40-12S1P5	9 ~ 18 VDC	1.5 VDC	0mA	8000mA	50mVp-p	110mA	1250mA	84	45000μF
FEC40-12S1P8	9 ~ 18 VDC	1.8 VDC	0mA	8000mA	50mVp-p	110mA	1538mA	82	37700μF
FEC40-12S2P5	9 ~ 18 VDC	2.5 VDC	0mA	8000mA	50mVp-p	110mA	2083mA	84	27000μF
FEC40-12S3P3	9 ~ 18 VDC	3.3 VDC	0mA	8000mA	50mVp-p	175mA	2683mA	86	21000μF
FEC40-12S05	9 ~ 18 VDC	5 VDC	0mA	8000mA	50mVp-p	225mA	4065mA	86	13600μF
FEC40-12S12	9 ~ 18 VDC	12 VDC	0mA	3333mA	75mVp-p	255mA	4065mA	86	2360μF
FEC40-12S15	9 ~ 18 VDC	15 VDC	0mA	2666mA	75mVp-p	310mA	4015mA	87	1510μF
FEC40-12D12	9 ~ 18 VDC	± 12 VDC	± 144mA	± 1800mA	120mVp-p	30mA	4444mA	85	± 1200μF
FEC40-12D15	9 ~ 18 VDC	± 15 VDC	± 112mA	± 1400mA	150mVp-p	35mA	4321mA	85	± 750μF
FEC40-12D3305	9 ~ 18 VDC	3.3 / 5 VDC	0mA	4A / 4A (total 8A) ^(1b)	100mVp-p	325mA	3416mA	85	11000 / 6800μF
FEC40-12T3312	9 ~ 18 VDC	3.3 / ±12 VDC	600mA / ±40mA	6000mA / ±400mA	50 / 75mVp-p	215mA	3063mA	84	13000 / ±330μF
FEC40-12T3315	9 ~ 18 VDC	3.3 / ±15 VDC	600mA / ±30mA	6000mA / ±300mA	50 / 75mVp-p	230mA	3000mA	84	13000 / ±110μF
FEC40-12T0512	9 ~ 18 VDC	5 / ±12 VDC	600mA / ±40mA	6000mA / ±400mA	50 / 75mVp-p	280mA	4024mA	86	6800 / ±330μF
FEC40-12T0515	9 ~ 18 VDC	5 / ±15 VDC	600mA / ±30mA	6000mA / ±300mA	50 / 75mVp-p	255mA	3963mA	86	6800 / ±110μF
FEC40-24S1P5	18 ~ 36 VDC	1.5 VDC	0mA	8000mA	50mVp-p	40mA	649mA	81	45000μF
FEC40-24S1P8	18 ~ 36 VDC	1.8 VDC	0mA	8000mA	50mVp-p	40mA	759mA	83	37700μF
FEC40-24S2P5	18 ~ 36 VDC	2.5 VDC	0mA	8000mA	50mVp-p	40mA	1016mA	86	27000μF
FEC40-24S3P3	18 ~ 36 VDC	3.3 VDC	0mA	8000mA	50mVp-p	60mA	1325mA	87	21000μF
FEC40-24S05	18 ~ 36 VDC	5 VDC	0mA	8000mA	50mVp-p	80mA	1961mA	89	13600μF
FEC40-24S12	18 ~ 36 VDC	12 VDC	0mA	3333mA	75mVp-p	70mA	2048mA	88	2360μF
FEC40-24S15	18 ~ 36 VDC	15 VDC	0mA	2666mA	75mVp-p	85mA	1985mA	89	1510μF
FEC40-24D12	18 ~ 36 VDC	± 12 VDC	± 144mA	± 1800mA	120mVp-p	20mA	2169mA	87	± 1200μF
FEC40-24D15	18 ~ 36 VDC	± 15 VDC	± 112mA	± 1400mA	150mVp-p	20mA	2108mA	87	± 750μF
FEC40-24D3305	18 ~ 36 VDC	3.3 / 5 VDC	0mA	4A / 4A (total 8A) ^(1b)	100mVp-p	80mA	1689mA	86	11000 / 6800μF
FEC40-24T3312	18 ~ 36 VDC	3.3 / ±12 VDC	600mA / ±40mA	6000mA / ±400mA	50 / 75mVp-p	65mA	1512mA	85	13000 / ±330μF
FEC40-24T3315	18 ~ 36 VDC	3.3 / ±15 VDC	600mA / ±30mA	6000mA / ±300mA	50 / 75mVp-p	65mA	1481mA	85	13000 / ±110μF
FEC40-24T0512	18 ~ 36 VDC	5 / ±12 VDC	600mA / ±40mA	6000mA / ±400mA	50 / 75mVp-p	60mA	1989mA	87	6800 / ±330μF
FEC40-24T0515	18 ~ 36 VDC	5 / ±15 VDC	600mA / ±30mA	6000mA / ±300mA	50 / 75mVp-p	75mA	1958mA	87	6800 / ±110μF
FEC40-48S1P5	36 ~ 75 VDC	1.5 VDC	0mA	8000mA	50mVp-p	25mA	321mA	82	45000μF
FEC40-48S1P8	36 ~ 75 VDC	1.8 VDC	0mA	8000mA	50mVp-p	25mA	375mA	84	37700μF
FEC40-48S2P5	36 ~ 75 VDC	2.5 VDC	0mA	8000mA	50mVp-p	25mA	508mA	86	27000μF
FEC40-48S3P3	36 ~ 75 VDC	3.3 VDC	0mA	8000mA	50mVp-p	35mA	655mA	88	21000μF
FEC40-48S05	36 ~ 75 VDC	5 VDC	0mA	8000mA	50mVp-p	40mA	969mA	90	13600μF
FEC40-48S12	36 ~ 75 VDC	12 VDC	0mA	3333mA	75mVp-p	50mA	1000mA	89	2360μF
FEC40-48S15	36 ~ 75 VDC	15 VDC	0mA	2666mA	75mVp-p	50mA	992mA	89	1510μF
FEC40-48D12	36 ~ 75 VDC	± 12 VDC	± 144mA	± 1800mA	120mVp-p	15mA	1084mA	87	± 1200μF
FEC40-48D15	36 ~ 75 VDC	± 15 VDC	± 112mA	± 1400mA	150mVp-p	15mA	1054mA	87	± 750μF
FEC40-48D3305	36 ~ 75 VDC	3.3 / 5 VDC	0mA	4A / 4A (total 8A) ^(1b)	100mVp-p	45mA	823mA	88	11000 / 6800μF
FEC40-48T3312	36 ~ 75 VDC	3.3 / ±12 VDC	600mA / ±40mA	6000mA / ±400mA	50 / 75mVp-p	35mA	747mA	86	13000 / ±330μF
FEC40-48T3315	36 ~ 75 VDC	3.3 / ±15 VDC	600mA / ±30mA	6000mA / ±300mA	50 / 75mVp-p	35mA	732mA	86	13000 / ±110μF
FEC40-48T0512	36 ~ 75 VDC	5 / ±12 VDC	600mA / ±40mA	6000mA / ±400mA	50 / 75mVp-p	30mA	982mA	88	6800 / ±330μF
FEC40-48T0515	36 ~ 75 VDC	5 / ±15 VDC	600mA / ±30mA	6000mA / ±300mA	50 / 75mVp-p	40mA	967mA	88	6800 / ±110μF

Note

- BELLCORE TR-NWT-000332. Case I: 50% Stress, Temperature at 40°C.
MIL-HDBK-217F Notice2 @Ta=25 °C, Full load(Ground, Benign, controlled environment).
- Maximum value at nominal input and full load.
- Typical value at nominal input and no load.
- Typical value at nominal input and full load.
- Test by minimum input and constant resistive load.
- The output requires minimum loading on the output to maintain specified regulation. Operation in no-load condition will not damage these devices, however they may not meet all listed specification.
- For the single output: Maximum output deviation is 10% inclusive of remote sense and trim. If remote sense is not being used, the +SENSE should be connected to its corresponding +OUTPUT and likewise the -SENSE should be connected to its corresponding -OUTPUT.
- Load regulation for triple output:
Main output(V1):10 to 100% with 10% to 100% balanced on auxiliaries.
Auxiliary outputs(V2 and V3):10% to 100% balanced on all outputs.
- Cross regulation for dual output: asymmetrical load 25% / 100% FL.
Cross regulation for triple output:
Main output 100% load, auxiliary 100%, other auxiliary 25% to 100%.
Auxiliary outputs(V2 and V3):main output 100% load, auxiliary 100%, other auxiliary 25% to 100% or main output 25%,auxiliary 25%,other auxiliary 25% to 100%.
- The models of FEC40-XXD3305 are specified with a 1uF ceramic output capacitors.
- Switching frequency for dual output: master (5VDC output) 300KHz slave (3.3VDC output) 500KHz
- The CTRL pin voltage is referenced to -INPUT.
- Heat-sink is optional and P/N : 7G-0026C-F.
- The FEC40 series can meet EN55022 Class A with parallel an external capacitor to the input pins.
Recommend: 12VDC input : 6.8μF/50V 1812 MLCC ; 24VDC input : 6.8μF/50V 1812 MLCC ; 48VDC input : 2.2μF/100V 1812 MLCC.
- An external input filter capacitor is required if the module has to meet EN61000-4-4, EN61000-4-5.
The filter capacitor Power Mate suggest: Nippon chemi-con KY series, 220 μ F/100V, ESR 48mΩ.
- Any condition of dual output (3.3VDC output / 5VDC output) rated lout current, not to exceed 8A of total output currents. The product safety approval pending.

CAUTION: This power module is not internally fused. An input line fuse must always be used.


Recommended EMI Filter:



Recommended Filter for EN55022 Class B Compliance


The components used in the above figure, together with the manufacturers' part numbers for these components, are as follows:

	C1	C2	C3	C4	C5 & C6	L1
FEC40-12xxx	4.7μF/50V 1812 MLCC	N/A	4.7μF/50V 1812 MLCC	N/A	1000pF/2KV MLCC	450μH Common Choke PMT-048
FEC40-24xxx	6.8μF/50V 1812 MLCC	N/A	6.8μF/50V 1812 MLCC	N/A	1000pF/2KV MLCC	450μH Common Choke PMT-048
FEC40-48xxx	2.2μF/100V 1812 MLCC	2.2μF/100V 1812 MLCC	2.2μF/100V 1812 MLCC	2.2μF/100V 1812 MLCC	1000pF/2KV MLCC	830μH Common Choke PMT-053



Recommended EN55022 Class B Filter Circuit Layout

Mechanical Drawing:



1. All dimensions in Inch (mm)
Tolerance: X.XX±0.02 (X.X±0.5)
X.XXX±0.01 (X.XX±0.25)
2. Pin pitch tolerance ±0.01(0.25)
3. Pin dimension tolerance ±0.004 (0.1)

PIN CONNECTION

PIN	SINGLE	DUAL	DUAL POSITIVE	TRIPLE
1	+INPUT	+INPUT	+INPUT	+INPUT
2	-INPUT	-INPUT	-INPUT	-INPUT
3	CTRL	CTRL	CTRL	CTRL
4	NC	NO PIN	3.3V	+AUX
5	-SENSE (Note 7)	+OUTPUT	COMMON	COMMON
6	+SENSE (Note 7)	COMMON	NC	-AUX
7	+OUTPUT	COMMON	NC	+OUTPUT
8	-OUTPUT	-OUTPUT	5V	COMMON
9	TRIM	TRIM	COMMON	NC

EXTERNAL OUTPUT TRIMMING

Output can be externally trimmed by using the method shown below.
() for dual output trim

